

技术参数 Technical Parameters

MODEL	QT4-15	QT5-15	QT6-15	QT7-15	QT8-15	QT10-15	QT12-15	
Vibration Frequency	3500-4500HZ	3500-4500HZ	3500-4500HZ	3500-4500HZ	3500-4500HZ	3500-4500HZ	3500-4500HZ	
Gross weight	7500kg	10500kg	11000kg	12000kg	12000kg	14500kg	15000kg	
Dimension	8800x1620x2800mm	9450x3600x2800mm	9450x3300x2700mm	9800x3600x2800mm	9800x3600x2800mm	11500x4050x2800mm	11500x4550x2800mm	
Power	36kw	42kw	42kw	42kw	49kw	56kw	92kw	
Cycle time	15-23s	15-23s	15-23s	15-23s	15-23s	15-23s	15-23s	
Rated pressure	16Mpa	21Mpa	21Mpa	21Mpa	21Mpa	21Mpa	21Mpa	
Vibration force	40KN	68KN	68KN	95KN	95KN	105KN	150KN	
Pallet size	920x530mm	1100x580mm	980x680mm	1150x750mm	980x880-900mm	1100x900-950mm	1350x950	
Vibration Type	振动加压成型hydraulic vibration							
Hollow Block	390×190×190mm	4PCS/MOULD/8HOURS 5760-7680/PCS	5PCS/MOULD/8HOURS 7200-9600/PCS	6PCS/MOULD/8HOURS 8640-11520/PCS	7PCS/MOULD/8HOURS 11000-15000/PCS	8PCS/MOULD/8HOURS 11520-15360/PCS	10PCS/MOULD/8HOURS 14400-19200/PCS	12PCS/MOULD/8HOURS 19008-25344/PCS
Porous Block	240×115×90mm	14PCS/MOULD/8HOURS 20160-26880/PCS	16PCS/MOULD/8HOURS 23040-30720/PCS	15PCS/MOULD/8HOURS 21600-28800/PCS	20PCS/MOULD/8HOURS 30000-40000/PCS	21PCS/MOULD/8HOURS 30240-40320/PCS	24PCS/MOULD/8HOURS 34560-46080/PCS	30PCS/MOULD/8HOURS 47520-63360/PCS
Solid Brick	240×115×51mm	28PCS/MOULD/8HOURS 37440-49920/PCS	34PCS/MOULD/8HOURS 48960-65280/PCS	36PCS/MOULD/8HOURS 46080-61440/PCS	42PCS/MOULD/8HOURS 68000-90000/PCS	45PCS/MOULD/8HOURS 67500-90000/PCS	51PCS/MOULD/8HOURS 73440-97920/PCS	63PCS/MOULD/8HOURS 99292-133056/PCS
Holland Paver	200×100×60mm	16PCS/MOULD/8HOURS 18200-23100/PCS	18PCS/MOULD/8HOURS 23400-29700/PCS	24PCS/MOULD/8HOURS 27300-34560/PCS	30PCS/MOULD/8HOURS 42000-54000/PCS	32PCS/MOULD/8HOURS 44352-59136/PCS	36PCS/MOULD/8HOURS 46800-59400/PCS	42PCS/MOULD/8HOURS 60060-76230 /PCS